



Solid Steel 60 Case™ QUICK™ Shafts

(HRC 60 Minimum)

Catalog Number					
Length in.	Nominal Diameter				
	1/4	3/8	1/2	5/8	3/4
6	TQS1/4L-6	TQS3/8L-6	TQS1/2L-6	TQS5/8L-6	TQS3/4L-6
9	TQS1/4L-9	TQS3/8L-9	TQS1/2L-9	TQS5/8L-9	TQS3/4L-9
12	TQS1/4L-12	TQS3/8L-12	TQS1/2L-12	TQS5/8L-12	TQS3/4L-12
15	TQS1/4L-15	TQS3/8L-15	TQS1/2L-15	TQS5/8L-15	TQS3/4L-15
18	TQS1/4L-18	TQS3/8L-18	TQS1/2L-18	TQS5/8L-18	TQS3/4L-18
24	TQS1/4L-24	TQS3/8L-24	TQS1/2L-24	TQS5/8L-24	TQS3/4L-24
30	TQS1/4L-30	TQS3/8L-30	TQS1/2L-30	TQS5/8L-30	TQS3/4L-30
36	TQS1/4L-36	TQS3/8L-36	TQS1/2L-36	TQS5/8L-36	TQS3/4L-36
42	TQS1/4L-42	TQS3/8L-42	TQS1/2L-42	TQS5/8L-42	TQS3/4L-42
48	TQS1/4L-48	TQS3/8L-48	TQS1/2L-48	TQS5/8L-48	TQS3/4L-48
60	—	—	TQS1/2L-60	TQS5/8L-60	TQS3/4L-60
72	—	—	TQS1/2L-72	TQS5/8L-72	TQS3/4L-72

Catalog Number					
Length in.	Nominal Diameter				
	1	1-1/4	1-1/2	1-3/4	2
12	TQS1L-12	TQS1-1/4L-12	TQS1-1/2L-12	TQS1-3/4L-12	TQS2L-12
18	TQS1L-18	TQS1-1/4L-18	TQS1-1/2L-18	TQS1-3/4L-18	TQS2L-18
24	TQS1L-24	TQS1-1/4L-24	TQS1-1/2L-24	TQS1-3/4L-24	TQS2L-24
30	TQS1L-30	TQS1-1/4L-30	TQS1-1/2L-30	TQS1-3/4L-30	TQS2L-30
36	TQS1L-36	TQS1-1/4L-36	TQS1-1/2L-36	TQS1-3/4L-36	TQS2L-36
42	TQS1L-42	TQS1-1/4L-42	TQS1-1/2L-42	TQS1-3/4L-42	TQS2L-42
48	TQS1L-48	TQS1-1/4L-48	TQS1-1/2L-48	TQS1-3/4L-48	TQS2L-48
60	TQS1L-60	TQS1-1/4L-60	TQS1-1/2L-60	TQS1-3/4L-60	TQS2L-60
72	TQS1L-72	TQS1-1/4L-72	TQS1-1/2L-72	TQS1-3/4L-72	TQS2L-72

SPECIFICATIONS			
Nominal Diameter	Class "L" O.D. Tolerance	Min. Depth of Hardness	Weight (lbs/inch of length)
1/4	.2495/.2490	.027	.014
3/8	.3745/.3740	.027	.031
1/2	.4995/.4990	.040	.055
5/8	.6245/.6240	.040	.086
3/4	.7495/.7490	.060	.125
1	.9995/.9990	.080	.222
1-1/4	1.2495/1.2490	.080	.348
1-1/2	1.4994/1.4989	.080	.500
1-3/4	1.7495/1.7490	.100	.681
2	1.9994/1.9987	.100	.890