



METRIC

Solid Steel, 60 Case™ QUICK™ Shafts

(h6) HRC 60 Minimum

Catalog Number					
Length mm	Nominal Diameter mm				
	5	8	10	12	16
200	TQSM5L-200MM	TQSM8L-200MM	—	—	—
400	TQSM5L-400MM	TQSM8L-400MM	—	—	—
500	—	—	TQSM10L-500MM	—	TQSM16L-500MM
600	TQSM5L-600MM	TQSM8L-600MM	—	—	TQSM16L-1000MM
800	TQSM5L-800MM	TQSM8L-800MM	—	—	TQSM16L-1200MM
1000	—	—	TQSM10L-1000MM	TQSM12L-1000MM	TQSM16L-1500MM
2000	—	—	—	TQSM12L-2000MM	TQSM16L-2000MM

Catalog Number				
Length mm	Nominal Diameter mm			
	20	25	30	40
500	TQSM20L-500MM	TQSM25L-500MM	TQSM30L-500MM	TQSM40L-500MM
600	TQSM20L-1000MM	TQSM25L-1000MM	TQSM30L-1000MM	TQSM40L-1000MM
800	TQSM20L-1200MM	TQSM25L-1200MM	TQSM30L-1200MM	TQSM40L-1200MM
1000	TQSM20L-1500MM	TQSM25L-1500MM	TQSM30L-1500MM	TQSM40L-1500MM
2000	TQSM20L-2000MM	TQSM25L-2000MM	TQSM30L-2000MM	TQSM40L-2000MM

SPECIFICATIONS			
Nominal Diameter mm	Class "L" O.D. Tolerance mm (inch)	Min. Depth of Hardness mm (inch)	Weight g/mm of length (lbs/inch of length)
5	5.00/4.99 (.1969/.1965)	0.69 (.027)	0.161 (.009)
8	8.00/7.99 (.3150/.3146)	0.69 (.027)	0.393 (.022)
10	10.00/9.99 (.3937/.3932)	0.69 (.027)	0.625 (.035)
12	12.00/11.99 (.4724/.4720)	1.02 (.040)	0.893 (.050)
16	16.00/15.99 (.6299/.6295)	1.02 (.040)	1.571 (.088)
20	20.00/19.99 (.7874/.7869)	1.52 (.060)	2.464 (.138)
25	25.00/24.99 (.9843/.9838)	2.03 (.080)	3.857 (.216)
30	30.00/29.99 (1.1811/1.1806)	2.03 (.080)	5.554 (.311)
40	40.00/39.99 (1.5748/1.5743)	2.03 (.080)	9.875 (.553)

Dimensions in parentheses are in inches.