



Solid Steel Chrome Plated 60 Case™ QUICK™ Shafts with Plain Ends

(HRC 60 Minimum)

Catalog Number			
Length in.	Nominal Diameter		
	1/2	5/8	3/4
6	TQS1/2CPL-6	—	TQS3/4CPL-6
12	TQS1/2CPL-12	—	TQS3/4CPL-12
18	TQS1/2CPL-18	TQS5/8CPL-18	TQS3/4CPL-18
24	TQS1/2CPL-24	TQS5/8CPL-24	TQS3/4CPL-24
36	TQS1/2CPL-36	TQS5/8CPL-36	TQS3/4CPL-36
48	TQS1/2CPL-48	—	TQS3/4CPL-48

Catalog Number			
Length in.	Nominal Diameter		
	1	1-1/4	1-1/2
6	TQS1CPL-6	—	—
12	TQS1CPL-12	—	—
18	TQS1CPL-18	—	TQS1-1/2CPL-18
24	TQS1CPL-24	TQS1-1/4CPL-24	TQS1-1/2CPL-24
36	TQS1CPL-36	TQS1-1/4CPL-36	TQS1-1/2CPL-36
48	TQS1CPL-48	TQS1-1/4CPL-48	TQS1-1/2CPL-48

SPECIFICATIONS			
Nominal Diameter	Class "L" O.D. Tolerance	Min. Depth of Hardness	Weight (lbs/inch of length)
1/2	.4995/.4990	.040	.055
5/8	.6245/.6240	.040	.086
3/4	.7495/.7490	.060	.125
1	.9995/.9990	.080	.222
1-1/4	1.2495/1.2490	.080	.348
1-1/2	1.4994/1.4989	.080	.500