



Solid 440C Stainless Steel 60 Case™ Quick™ Shafts (HRC 50-55)

Catalog Number					
Length in.	Nominal Diameter				
	1/4	3/8	1/2	5/8	3/4
6	TQS1/4SSL-6	TQS3/8SSL-6	TQS1/2SSL-6	TQS5/8SSL-6	TQS3/4SSL-6
12	TQS1/4SSL-12	TQS3/8SSL-12	TQS1/2SSL-12	TQS5/8SSL-12	TQS3/4SSL-12
18	TQS1/4SSL-18	TQS3/8SSL-18	TQS1/2SSL-18	TQS5/8SSL-18	TQS3/4SSL-18
24	TQS1/4SSL-24	TQS3/8SSL-24	TQS1/2SSL-24	TQS5/8SSL-24	TQS3/4SSL-24
36	TQS1/4SSL-36	TQS3/8SSL-36	TQS1/2SSL-36	TQS5/8SSL-36	TQS3/4SSL-36
48	TQS1/4SSL-48	TQS3/8SSL-48	TQS1/2SSL-48	TQS5/8SSL-48	TQS3/4SSL-48

Catalog Number				
Length in.	Nominal Diameter			
	1	1-1/4	1-1/2	2
6	—	—	—	—
12	TQS1SSL-12	TQS1-1/4SSL-12	TQS1-1/2SSL-12	—
18	TQS1SSL-18	TQS1-1/4SSL-18	TQS1-1/2SSL-18	—
24	TQS1SSL-24	TQS1-1/4SSL-24	TQS1-1/2SSL-24	TQS2SSL-24
36	TQS1SSL-36	TQS1-1/4SSL-36	TQS1-1/2SSL-36	TQS2SSL-36
48	TQS1SSL-48	TQS1-1/4SSL-48	TQS1-1/2SSL-48	TQS2SSL-48
60	—	TQS1-1/4SSL-60	TQS1-1/2SSL-60	TQS2SSL-60

SPECIFICATIONS			
Nominal Diameter	Class "L" O.D. Tolerance	Min. Depth of Hardness	Weight (lbs/inch of length)
1/4	.2495/.2490	.027	.014
3/8	.3745/.3740	.027	.031
1/2	.4995/.4990	.040	.055
5/8	.6245/.6240	.040	.086
3/4	.7495/.7490	.060	.125
1	.9995/.9990	.080	.222
1-1/4	1.2495/1.2490	.080	.348
1-1/2	1.4995/1.4989	.080	.500
2	1.9994/1.9987	.100	.890